

In the Claims:

1 1. [Previously Presented] An image forming device comprising:
2 an image engine configured to form hard images;
3 an environmental sensor configured to monitor at least one environmental
4 condition proximate to the image forming device and to provide data indicative
5 of the at least one environmental condition;
6 an interface configured to communicate the data indicative of the at least
7 one environmental condition externally of the image forming device;
8 a memory; and
9 processing circuitry configured to control storage of the data using the
10 memory to provide a history of the at least one environmental condition to
11 which the image forming device has been exposed.

1 2. [Original] The device of claim 1 wherein the image engine is
2 configured to use a consumable to form the hard images, and the interface
3 comprises a memory of the consumable.

1 3. [Original] The device of claim 1 wherein the interface comprises a
2 communications interface adapted to communicate with devices external of the
3 image forming device.

1 4. [Original] The device of claim 1 further comprising processing
2 circuitry configured as an embedded web server and configured to communicate
3 the data with respect to a client device external of the image forming device.

1 5. Canceled.

1 6. [Previously Presented] The device of claim 1 wherein the
2 processing circuitry is configured to control the storage of the data at a
3 predetermined moment in time.

1 7. [Previously Presented] The device of claim 1 wherein the
2 processing circuitry is configured to monitor the data and to control the storage
3 of the data responsive to the monitoring.

1 8. [Original] The device of claim 1 further comprising an internal
2 power source configured to provide power to the sensor in an absence of power
3 from a source external of the image forming device.

1 9. [Original] The device of claim 1 wherein the environmental sensor
2 is configured to monitor the at least one environmental condition comprising a
3 plurality of environmental conditions proximate to the image forming device and
4 comprising humidity and temperature.

1 10. [Original] The device of claim 1 wherein the image engine
2 comprises a print engine of the image forming device embodied as a printer.

1 11. [Previously Presented] A method of operating an image forming
2 device, the method comprising:
3 providing an image forming device configured to form hard images;
4 sensing at least one environmental condition of an environment proximate
5 to the image forming device;
6 communicating data regarding the at least one environmental condition
7 externally of the image forming device; and
8 receiving a request within the image forming device from a source
9 external of the image forming device, and the communicating comprises
10 communicating responsive to the receiving.

1 12. Canceled.

1 13. Canceled.

1 14. [Original] The method of claim 11 wherein the sensing comprises
2 sensing a plurality of environmental conditions comprising temperature and
3 humidity.

1 15. [Original] The method of claim 11 wherein the providing comprises
2 providing the image forming device embodied as a printer.

1 16. [Previously Presented] A method of monitoring an environment
2 proximate to an image forming device configured to form hard images, the
3 method comprising:

4 providing an image forming device configured to form hard images and to
5 monitor at least one environmental condition proximate to the image forming
6 device and to communicate data regarding the at least one environmental
7 condition externally of the image forming device;

8 receiving the data regarding the at least one environmental condition from
9 the image forming device; and

10 analyzing the data regarding the at least one environmental condition after
11 the receiving to determine a quantitative parameter for the at least one
12 environmental condition for testing other image forming devices.

1 17. Canceled.

1 18. [Original] The method of claim 16 further comprising
2 communicating a request to the image forming device, and wherein the
3 communicating the data is responsive to the communicating the request.

1 19. [Original] The method of claim 16 wherein the providing comprises
2 providing the image forming device configured to use a consumable, and
3 wherein the receiving the data comprises extracting the data from the
4 consumable.

1 20. [Original] The method of claim 16 wherein the providing comprises
2 providing the image forming device configured to monitor the at least one
3 environmental condition comprising a plurality of environmental conditions
4 comprising temperature and humidity.

1 21. [Previously Presented] An image forming device comprising:
2 an image engine configured to form hard images;
3 an environmental sensor configured to monitor at least one environmental
4 condition proximate to the image forming device and to provide data indicative
5 of the at least one environmental condition;
6 an interface configured to communicate the data indicative of the at least
7 one environmental condition externally of the image forming device; and
8 an internal power source configured to provide power to the sensor in an
9 absence of power from a source external of the image forming device.

1 22. Canceled.

1 23. [Previously Presented] An image forming device comprising:
2 an image engine configured to form hard images;
3 an environmental sensor configured to monitor at least one environmental
4 condition proximate to the image forming device and to provide data indicative
5 of the at least one environmental condition;
6 an interface configured to communicate the data indicative of the at least
7 one environmental condition externally of the image forming device; and
8 wherein the image engine is configured to use a consumable to form the
9 hard images, and the interface comprises a memory of the consumable.

1 24. [Previously Presented] The device of claim 1 wherein the data of
2 the history comprises a plurality of values for the at least one environmental
3 condition stored over a period of time.

1 25. [Previously Presented] The device of claim 1 further comprising an
2 internal power source configured to provide operational power to permit storage
3 of the data to provide the history of the at least one environmental condition
4 during an absence of power from a source external of the image forming device.

1 26. [Previously Presented] The method of claim 11 wherein the
2 providing comprises providing the image forming device configured to use a
3 consumable to form hard images, and the communicating comprises storing the
4 data regarding the at least one environmental condition using the consumable.

1 27. [Previously Presented] The method of claim 16 wherein the
2 quantitative parameter comprises a temperature range.

1 28. [Previously Presented] An image forming device testing method
2 comprising:
3 providing a first image forming device to be tested;
4 accessing a history comprising data indicative of at least one
5 environmental condition to which at least one second image forming device has
6 been exposed;
7 determining at least one testing criteria responsive to the accessing of the
8 history; and
9 testing the first image forming device using the testing criteria after the
10 determining.

1 29. [New] The device of claim 1 wherein the processing circuitry is
2 configured to control outputting of the history externally of the image forming
3 device.

1 30. [New] The device of claim 1 wherein the processing circuitry is
2 configured to control outputting of the history comprising a plurality of values
3 indicative of the at least one environmental condition obtained at a plurality of
4 different moments of time.

1 31. [New] The device of claim 1 wherein the memory is configured to
2 store the history prior to the image forming device being implemented for the
3 first time to form hard images.

1 32. [New] The method of claim 11 wherein the communicating
2 comprises outputting the data regarding the at least one environmental condition
3 externally of the image forming device.

1 33. [New] The method of claim 16 further comprising outputting the
2 data regarding the at least one environmental condition externally of the image
3 forming device.

1 34. [New] The device of claim 21 wherein the interface is configured
2 to output the data indicative of the at least one environmental condition
3 externally of the image forming device.

1 35. [New] The device of claim 23 wherein the interface is configured
2 to output the data indicative of the at least one environmental condition
3 externally of the image forming device.